

The DBW-5 is a small winch model typically recommended for low cable capacity applications that can tolerate lower line speeds. The DBW-5V is a “vertical” variation of the frame that offers a slightly smaller footprint compared to the default DBW-5.

The bolt-together plate-and-crossbar frame design helps lower the DBW-5/5V’s cost compared to equivalent welded-frame winches in A.G.O.’s lineup.

	DBW-5	DBW-5V
Typical dims*	38”L x 25”W x 20”H	29”L x 25”W x 36”H
Typical weight*	~250 lbs	~300 lbs
Standard supported power sources	110VAC or 220VAC single-phase power	

* Dimensions do not include slip ring width. Weight does not include drum cable. Dimensions and weight are only approximate and will vary depending on each winch’s specific drum, drivetrain, and feature configuration.

Features and add-ons

Dog clutch for freewheeling	Included
Drum pin lock	Included
Drum manual disk brake	Included
Manual backup auxiliary drivetrain	Included
Lifting handles for manual portability	Included
Levelwind	Add-on
Slip ring	Add-on
One-way drum ratchet	Add-on
Recovery assistance brake winch	Add-on
Encoder wire counting system	Not compatible
Tension-limiting slip clutch	Conditional add-on
Winch-mounted A-frame boom	Conditional add-on



Operation interface options

	Local	Wired remote	Dual
Simple controls	Included	Upgrade	Upgrade
Joystick	Not compatible	Upgrade	Not compatible
Belly pack	Not compatible		

#10-626 Esquimalt Rd
Victoria, BC, Canada, V9A3L4

info@agoenvironmental.com

T: +1 (250) 386-4015